

Ururu streamer technology air purifier

MCK55W



Ururu -
humidification



Flash Streamer

Humidification and air purification in one

- › Humidification and purification in one
- › Pure air thanks to air purification technologies
- › Catches fine particles of dust
- › Powerful suction and whisper quiet
- › New stylish and compact design

MCK55W



MCK55WVM

Single Unit		MCK		55W	
Application		Floor standing type			
Applicable room area		m ²		41	
Dimensions	Unit	HeightxWidthxDepth		700 x270 x270	
Weight	Unit	kg		9.5	
Casing	Colour	White			
Fan	Type	Multi Blade Fan (Sirocco fan)			
Air flow rate	Air purifying operation	Silent/Low/Medium/Turbo	m ³ /h	54 /120 /192 /330	
	Humidifying operation	Silent/Low/Medium/Turbo	m ³ /h	102 /144 /192 /330	
Sound pressure level	Air purifying operation	Silent/Low/Medium/Turbo	dBA	19.0 /29.0 /39.0 /53.0	
	Humidifying operation	Silent/Low/Medium/Turbo	dBA	25.0 /33.0 /39.0 /53.0	
Humidifying operation	Power input	Silent/L/M/Turbo	kW	0.011 /0.014 /0.019 /0.058	
	Humidification	Silent/Low/Medium/Turbo	ml/h	200 /240 /300 /500	
	Water tank capacity		l	2.7	
Air purifying operation	Power input	Silent/L/M/Turbo	kW	0.007 /0.010 /0.017 /0.056	
Deodorizing method		Flash streamer + Deodorizing catalyst			
Dust collecting method		Electrostatic HEPA filter			
Air filter	Type	Polyethylene terephthalate net			
Sign	Item	01	Dust:3 stages / Odour:3 stages / Anti-pollen mode / Water supply lamp / Child proof lock lamp / ON/OFF lamp / Streamer lamp / Econo mode / MOIST mode / AUTO FAN mode / PM2.5 sensor lamp:3 stages / Humidity monitor lamp:5 stages / Humidity setting: Low/Standard/High / Airflow rate: Quiet/Low/Standard/Turbo / Humidity on/		
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/60/220-240/220-230	
Type	Humidifying air purifier				

The applicable room area is appropriate for operating the unit of maximum fan speed (HH). Applicable room area indicates the space where a certain amount of dust particles can be removed in 30 minutes. (JEM 1467) | Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. | Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) | Electrostatic HEPA filter and humidifying filters are attached in the unit.

Daikin Europe N.V. N.V. · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412.120.336 · Oostende (Responsible Editor)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

ECPEN20-701

02/2020

